

# **APPLICATIONS**

# FROM DATA LOGGERS TO TELEMETRY TO DATA SERVICES, IN-SITU IS YOUR SOURCE FOR THE MOST TRUSTED AND COMPLETE LINE OF WATER MONITORING PRODUCTS AND SERVICES.


In-Situ Inc. is a leading manufacturer of in-situ (on-site) water monitoring instruments for groundwater and surface water applications. Since 1976, we have provided water monitoring professionals with innovative solutions, such as the Aqua TROLL 500, with the industry's first mobile app, for low-flow groundwater sampling and environmental monitoring.

Our environmental monitoring solutions include high-accuracy water quantity, quality and flow instrumentations. We are also known for our products and services to support remote access to decision-quality data via easy integration with VuLink<sup>TM</sup>, our game-changing cellular telemetry device, and our cloud-based HydroVu<sup>TM</sup> Data Services platform.

In-Situ offers a full line of accurate, reliable water level data loggers and meters for any project and budget. Whether you need long-term monitoring or instant results, our fully sealed, solid-titanium Level TROLL® data loggers are built to last, saving you money and time in the field.

Our easy-to-use instruments, telemetry and data services platform are designed to work together, so even your most junior staff member can set up the equipment and get the data you need. It used to be a challenge to collect, analyze and share your data. But now, from your mobile device to your laptop to the cloud, your data is where you need it, when you need it.

Our team of experts can help you find the right solution for your project, and our support team is always standing by to offer complimentary, 24/7 technical support and mobile help in the field. We're also happy to rent our equipment to you, fully serviced, calibrated and ready to go.



# **LEVEL TROLL® DATA LOGGERS**

# Level TROLL® 400 Data Logger









Measures and logs water level, water pressure, and temperature in a maintenance-free system ideal for long-term monitoring at flood-prone or high-humidity sites. Sub-1 inch diameter.








- Available in non-vented (absolute) pressure ranges up to 1120 ft (341 m)
- Fully sealed, all titanium construction and sensors
- Flexible communication protocols (4-20 mA, SDI-12, RS-485)
- Low-power batteries last 10+ years

## Level TROLL® 500 Data Logger





- Available in vented (gauged) pressure ranges up to 1153 ft (351 m)
- Fully sealed, all titanium construction and sensors
- Flexible communication protocols (4-20 mA, SDI-12, RS-485)
- Low-power batteries last 10+ years

# Level TROLL® 700 Data Logger





- Available in pressure ranges up to 1,153 ft (351 m) for vented and 2,274 ft (693 m) for non-vented
- Fully sealed, all titanium construction and sensors
- Automatic atmospheric compensation (vented models only)
- Advanced logging modes













# Level TROLL® 700H Data Logger



The most accurate water level data logger on the market, meeting the USGS surface water specification of ±0.01 foot. Continuous monitoring of water level, water pressure, and temperature.

- Available in vented (gauged) configuration in pressure ranges up to 35 ft (11 m)
- Automatic atmospheric compensation
- Advanced logging modes
- OSW-Compliant data to meet USGS Office of Surface Water specifications












# BaroTROLL® and Rugged BaroTROLL® Data Loggers







- Use the BaroTROLL with non-vented (absolute) Level TROLL 400 and 700, or Aqua TROLL 200
- Use the Rugged BaroTROLL with non-vented (absolute) Rugged TROLL 100 and 200 Data Loggers
- Titanium construction and 10-year internal battery
- Software post-corrects multiple data logger files from a single unit













# RUGGED TROLL® & CTD DATA LOGGERS, AND WATER LEVEL TAPES & METERS

# Rugged TROLL® 100 Data Logger









Our most economical option for measuring and logging water level, water pressure, and temperature.

- Available in non-vented (absolute) pressure ranges up to 250 ft (76 m)
- Titanium body with Delrin nose cone and backend
- Ceramic pressure sensor
- Download data via Rugged TROLL Docking Station (sold separately)

### Rugged TROLL® 200 Data Logger













Measures and logs water level, water pressure, and temperature, and features a cabled setup for direct read or telemetry data access.

- Available in non-vented (absolute) pressure ranges up to 250 ft (76 m)
- Titanium body with Delrin nose cone and backend
- Ceramic pressure sensor
- Download data via telemetry system, Rugged TROLL Docking Station, or direct-read cable (sold separately)

### Agua TROLL® 100 and 200 Data Loggers















Measure and record water level, water pressure, conductivity, and temperature with the Aqua TROLL 200, or only conductivity and temperature with the Aqua TROLL 100.

Unique conductivity cell allows for a wide, accurate measurement range in a narrow diameter instrument (sub-1 inch).

- $\bullet$  Full range conductivity with optimum accuracy 5 to 100,000  $\mu$ S/cm
- Dynamic density compensation on the Aqua TROLL 200
- Copper antifouling conductivity guard available; copper antifouling nose cone also available for the Aqua TROLL 200 only (both sold separately)
- Aqua TROLL 200 is available in pressure ranges up to 692 ft (210m) for vented or 658 ft (200m) for non-vented

# **Virtual HERMIT® Aquifer Testing Kit**

Connect multiple wells and program all data loggers at once to conduct step-drawdown tests and constant pump-rate tests across an entire well field. Available exclusively through In-Situ Rentals.

- Supports up to 15 wells per system
- Simultaneously configures, starts, displays, steps, or stops all connected data loggers
- Allows data downloads while tests are running
- Uses research-grade Level TROLL 700 Data Loggers

#### **Water Level Meters**

Durable, easy-to-read level meters in various lengths. Include static and drawdown modes.

- Water Level Meter 100: Economical water level tape with a Kevlar-reinforced polyethylene tape and stainless steel conductors
- Water Level Meter 200: Engineer-grade water level tape with high-tensile steel tape and stainless steel conductors; ASME-certified









# **REMOTE MONITORING SOLUTIONS**










**IN-DEPTH DATA ANALYSIS** 



#### **DATA SERVICES**

#### HydroVu<sup>™</sup> Data Services:

- Organize multiple projects, users, and instruments in one cloud-based location.
- Get secure, real-time access to decisionquality data anywhere, anytime.
- Simplify the task of filtering data for useful results.



#### **TELEMETRY**

- In-well device features one-press set up, expanded coverage, and two-to-five times the battery life of other devices.
- Free cellular data out of the box for a limited number of parameters and readings once per day, no set up required.
- Includes continuous GPS, encrypted connections, enhanced in-device alarms, desiccant-free operation, and IP68 waterproof rating.



#### **INSTRUMENTS**

#### **Water Level:**

- Vented and non-vented data loggers for every project and budget.
- Fully sealed, titanium design well-suited for even the harshest environments.
- Simple setup and data retrieval with field-ready connectors and intuitive software.

# **KEY FEATURES AND ACCESSORIES**



#### **ANTIFOULING**

Specially formulated copper antifouling guard and/or nose cone combats biofouling in coastal environments and high-fouling sites, improving the accuracy of your data and extending the length of deployment by up to six weeks.



# RUGGED CABLE AND RUGGED TROLL DIRECT-READ CABLE SYSTEMS

Durable, long-lasting cables come in custom lengths and provide real-time communication. Patented twist-lock connectors provide easy, secure attachment and detachment, protecting your investment.



#### **INTERNAL BATTERY POWER**

Internally sealed lithium battery power for frequent, fast sampling or long-term deployments. No external power is required, although it is an option (except on Rugged TROLL instruments).



#### **SPECIALIZED LOGGING MODES**

Advanced logging modes for specialized applications. In addition to linear, linear average, and event, these products also include step linear, fast linear, and true logarithmic modes.



#### **INTERNAL MEMORY**

Internal 4 MB memory stores up to 250,000 data points, and 2 MB memory stores up to 120,000 data points.



#### **TELEMETRY CAPABLE**

Remote monitoring made easy with secure and reliable in-well telemetry, featuring setup with one button press, global cellular coverage, and extraordinary power savings. Both alkaline and lithium batteries supported.



#### **NARROW-DIAMETER DESIGN**

Compact design fits narrow-diameter wells. Sub-1 inch diameter instruments measure 0.72 inches (1.83 cm), and sub-2 inch instruments measure 1.03 inches (2.62 cm).

# **ADDITIONAL ACCESSORIES**



#### **TUBING**

Polyethylene (PE) or Teflon-lined Polyethylene (TLPE) tubing available in 100 or 500 foot lengths. Silicone pump head tubing, size 15; available in 10, 25, and 500 foot (3.04, 7.62, 152.4 m) lengths.



#### **BAILERS**

Bailers for straight-forward collection and visual examination of water samples in different environments. Available in PVC, Polyurethane (weighted), and biodegradable models, and in 0.7 x 36 inch and 1.5 x 36 inch sizes.



#### **WELL CAPS**

Vented well caps and vented locking well caps for 2 or 4 inch wells. Expandable locking well caps for 2, 3, 4, 6, and 8 inch wells.



#### **PUMPS**

Sampling, peristaltic, submersible, and portable bladder pumps available for rent through In-Situ Rentals.

For our full offering of accessories, please visit www.in-situ.com



#### **CALL OR CLICK TO PURCHASE OR RENT**

1-800-446-7488 (toll-free in U.S.A. and Canada) 1-970-498-1500 (U.S.A. and international)

www.in-situ.com

221 East Lincoln Avenue, Fort Collins, CO 80524 USA Copyright © 2022 In-Situ Inc. All rights reserved. June 2022.