



## Aquaculture Management System

**THE WIRELESS IN-SITU AQUACULTURE SYSTEM AUTOMATES OXYGEN MONITORING AND CONTROL. THE SYSTEM INCLUDES SOLAR-POWERED BUOYS, AERATOR CONTROLLERS, AND SOFTWARE. EASY TO INSTALL, ALARMS WHEN SYSTEM NEEDS MAINTENANCE, AND AUTOMATES OXYGEN MANAGEMENT.**

The Aquaculture Pond Buoy allows easy remote monitoring of dissolved oxygen levels and temperature in aquaculture pond raceways. The solar-powered buoy has an easy-to-use optical RDO® Titan probe for 24-hour dissolved oxygen monitoring, plus a transceiver that transmits data wirelessly, right to your laptop or PC.

### **SAVES MONEY**

- **Improves fish production**—consistent control of oxygen can improve feed conversion ratios, minimize fish stress, and reduce fish disease and mortality.
- **Reduces calibration and maintenance**—RDO Titan Probe stays calibrated for an entire season. Automated cleaning system removes fouling.
- **Reduces manual oxygen checks**—drive less and stay informed of oxygen levels in every pond—24 hours a day.

- **Installs quickly**—a wireless 20-pond system (10-12 acre ponds) can be installed in one day.
- **Improves aeration control**—automated control can reduce energy expenses and wear on equipment
- **Qualifies for grants and credits**—USDA grants for energy efficient systems and solar tax credits reduce costs.

### **MINIMIZES RISK**

- **Obtains fast, stable results**—the RDO Titan Probe responds quickly to changes and is not susceptible to drift.
- **Alerts sent to phone, email, or text message**—receive real-time updates—anywhere, anytime.
- **Reduces failures**—wireless operation reduces potential damage from lightning strikes, mowers, and exposure.
- **Monitors aerator operation**—the system continuously reports amperage draw of aerator motors.
- **Tracks pond temperature**—when temperatures exceed optimal levels, you can verify eligible loss of inventory.

**HEALTHY WATER | HEALTHY FISH | HEALTHY PROFITS**

**[www.in-situ.com](http://www.in-situ.com)**

CALL OR CLICK TO PURCHASE OR RENT  
1-800-446-7488 (toll-free in U.S.A. and Canada)  
1-970-498-1500 (U.S.A. and international)

### **Applications:**

- **POND AQUACULTURE**
- **TANK AQUACULTURE**



## RDO TITAN OXYGEN PROBE

SENSOR TYPE	Optical dissolved oxygen sensor Ships with the RDO Classic Sensor Cap
RANGE, DO	0 to 60 mg/L
ACCURACY, DO	±0.1 mg/L, 0 to 20 mg/L ±2% of reading, 20 to 60 mg/L
RESOLUTION, DO	0.01 mg/L
RESPONSE TIME, CAP	T90: <45 sec. T95: <60 sec. @ 25° C
RANGE, TEMP.	0° to 50° C (32° to 122° F)
ACCURACY, TEMP.	±0.1° C typical
RESOLUTION, TEMP.	0.01° C
SALINITY COMP.	Fixed or real-time capable
BAROMETRIC COMP.	Fixed or real-time capable
METHODS	EPA-approved In-Situ® RDO methods 1002-8-2009, 1003-8-2009, 1004-8-2009 Standard Methods 4500-O

## ENVIRONMENTAL RATINGS

PRESSURE	150 psi from 0° to 50° C; 300 psi @ 25° C
DEPTH	689 ft (210 m) @ 25° C
OPERATING TEMP.	Probe: 0° to 50° C (32° to 122° F)
STORAGE TEMP.	Sensor cap: 1° to 60° C (33° to 140° F), in factory container Probe: -5° to 60° C (23° to 140° F)
IP RATING	IP-67 with cap off; IP-68 with cap installed

## GENERAL RATINGS

CAP LIFE	12 months typical
CAP SHELF LIFE	36 months
COMM. OUTPUT	Modbus/RS485
POWER REQUIREMENTS	8 to 36 VDC
POWER CONSUMPTION	Maximum: 50 mA at 12 VDC
CABLE LENGTHS	Modbus: Up to 1219 m (4000 ft)
CABLE CONNECTION	Detachable from probe
WARRANTY	Probe: 3 years from date of shipment

Specifications are subject to change without notice.

## OXYGEN MONITORING BUOY

The buoy is a self-contained, self-powered oxygen and temperature monitoring platform. Radio transmissions relay RDO Titan Probe readings to a base station. A site survey will determine radio and repeater requirements for your aquaculture operation.

OPERATING TEMP.	Buoy: -25° to 60° C (-13° to 140° F)
STORAGE TEMP.	Buoy: -10° to 60° C (14° to 140° F)
BUOY MATERIALS	Polyethylene float with PVC mountings and fittings
RADIO TYPE	Frequency hopping spread spectrum; site specific up to 11 km (7 mi)
SOLAR PANEL	10W
BATTERY	12V, 12 Ah, SLA
CHARGE CONTROLLER	4.5A, 12V
BRUSH MOTOR	12 VDC
BRUSH ENCLOSURE	PVC
DIMENSIONS	61 x 91.4 x 81.3 cm (24 x 36 x 32 in) (WxHxD)
WEIGHT	18 kg (40 lbs)
WARRANTY	1 year

## AERATOR CONTROLLER

The aerator controller is a radio-linked AC relay controller and AC current measuring system. Models are available with 4 or 8 AC relays with corresponding AC current sensor inputs.

OPERATING TEMP.	0° to 50° C (32° to 122° F)
STORAGE TEMP.	-10° to 60° C (14° to 140° F)
ENCLOSURE	Steel: Type 1, 3R Fiberglass: NEMA 4x
POWER, REQUIRED	100-240 VAC, 0.15 A, 50-60 Hz
AC RELAY OUTPUTS	24-240 VAC, 10A
CURRENT INPUTS	200 mA max.
CERTIFICATIONS	UL and CSA safety standards by ETL for use in general locations
DIMENSIONS	Steel: 31.8 x 33.8 x 16.5 cm (12.5 x 13.3 x 6.5 in) (WxHxD) Fiberglass: 30.0 x 35.1 x 17.8 cm (11.8 x 13.8 x 7.0 in)
WEIGHT	Steel: 10.3 kg (22.6 lbs) Fiberglass: 7.0 kg (15.5 lbs)
WARRANTY	1 year

## WIRELESS REPEATER

Use a wireless repeater to overcome physical obstructions or to increase range. A site survey will determine radio and repeater requirements.

RADIO TYPE	Frequency hopping spread spectrum; site specific up to 11 km (7 mi)
POWER OPTIONS	AC power supply or one 20 W solar panels
BATTERY	12 V, 12 Ah, SLA
CHARGE CONTROLLER	4.5 A, 12 V
WARRANTY	1 year

[www.in-situ.com](http://www.in-situ.com)

CALL OR CLICK TO PURCHASE OR RENT

1-800-446-7488 (toll-free in U.S.A. and Canada) • 1-970-498-1500 (U.S.A. and international)

221 East Lincoln Avenue, Fort Collins, CO 80524 USA

Copyright © 2018 In-Situ Inc. All rights reserved. September 2018