



## Required Components

- 1 Aqua TROLL 400 instrument
- 2 Wireless TROLL Com
- 3 Rugged Twist-Lock Cable
- 4 Bluetooth-enabled mobile device

## Getting Started

### 1 Install the sensors.



Twist the restrictor off the probe.



Locate the RDO sensor cap container and remove the cap.



Remove the dust cap from the RDO sensor.



Align the slotted edge of the RDO cap with the flat edge of the RDO sensor. Press the cap firmly into position.



Remove the orange plug from the pH/ORP sensor port.



Use the alignment marks to properly align the pH/ORP sensor with the port connection, and press firmly into place. Push until the sensor is completely inserted into the port.



Twist the restrictor back onto the probe.

## 2 Connect to the communication device.



Connect Rugged Cable to the Wireless TROLL Com and instrument.



Instrument is ready to pair with software. Turn on the Wireless TROLL Com.


## 3 Connect to the software.



Download and install the VuSitu mobile app from the Google Play store. Visit [play.google.com](http://play.google.com) on your Android device.




Turn on the Wireless TROLL Com and open VuSitu mobile app.



Select **Add New Device** when connecting for the first time.




Locate the serial number under the yellow lid on the Wireless TROLL Com.




From device's Bluetooth Settings screen, tap serial number of Wireless TROLL COM.

Select **Choose or Add a Device**.



Tap mobile device's back button and tap serial number from list.



Tap mobile device's **Back** button to view Connected Instrument screen.



VuSitu's on-screen instructions will guide you through instrument calibration, livereadings, log setup and data sharing.

**4**

## ***Learn more.***

Get complete instructions about calibration, logging and working with data in the product manual. Download it from [www.in-situ.com](http://www.in-situ.com).